



## **D14A / D14B**

### **▣ CABINET**

Top and front panels are molded of ABS plastic and side panels are made of electric zinccoated steel with high polymer polyester resin.

### **▣ COLOR**

Off White, Dark Gray, Wine Red

### **▣ FAUCETS**

Durable polypropylene. Self-closing type. Easy to operate.

### **▣ DRIP TRAY**

Concealed liftout design, high impact, durable ABS, Removable, anti-splash grid diverts drip water into receptacle.

### **▣ COLD WATER TANK**

Hygienic stainless steel.

### **▣ COLD WATER THERMOSTAT**

Temperature is controlled to 4°C~10°C by adjustable thermostat, easily accessible on back

### ▣REFRIGERATION UNIT

Convection cooled condenser, internally spring mounted hermetically sealed compressor with automatic overload protector. No lubricant needed. Refrigerant is controlled by accurately calibrated capillary tube.

### ▣HOT WATER TANK

Hygienic type stainless steel. Highly efficient internal heating element.  
Fire proof insulation.

### ▣HOT WATER THERMOSTAT

Water temperature is controlled to nearly 185°F(85°) by automatic, hot water ON/OFF switch is easily accessible on back.(Model D14A)

### ▣DUAL FLOAT VALVE

Water level is controlled with a Dual float valve. Dual float valve maintains water height in reservoir. Incoming water pressure range of 20~100psi.

### ▣ELECTRICAL

220V ~ 240V(±10%) 50/60Hz, 100V ~ 127V(±10%) 50/60Hz provided with power cord.  
Units of other power supplies available upon special order.

### ▣QUALITY

Our models covered by these specifications are manufactured to comply with the standards of overseas quality program.

### ▣WARRANTY

One year on the sealed refrigeration system and most component Part.

▣ **CONTAINER LOADING QUANTITY**

20FT-238pcs, 40FT-490pcs

▣ **PACKING**

Export standard carton packing.

▣ **REFRIGERANT TYPE**

R134a



Models	D14A(Hot&Cold)	D14B(Cook&Cold)
Cold Water	0.9GAL of 50°F/HR(3.5L of 10°C)	
Hot Water	1.71GAL of 185°F/HR (6.5L of 85±5°C)	NON
Room Temp. Water	NON	O
Dimensions	12.3"W(313mm) x 12.7"D(323mm) x 39.3"H(1000mm)	
Weight	32 lbs(16kg)	30 lbs(15kg)
Shipping Dimensions	12.5"W(320mm) x 12.9"D(330mm) x 40"H(1020mm)	
Shipping Weight	36 lbs(18kg)	34 lbs(17kg)

\* Cold and hot water: The above rates tested in ambient temperature-90°F(32°C),  
Water inlet temperature -80°F(27°C). Specifications are subject to change without notice.